RI4ING





SAFE

Grade A LiFePO₄ Cell RELIABLE

Compatible with Major PCS Brand

♦ CALABLE

Scalable From 10.5 To 737.1 kWh



Model	lite 10K5	AIR 11K7

Performance		
Nominal Voltage	51.2 Vdc	
Nominal Capacity	206 Ah	230 Ah
Battery Energy	10.5 kWh	11.7 kWh
Charge Current	100 A	
Charge Power	6.14 kWh	
Discharge Current	170 A	
Discharge Power	8.7 kW	
Short Circuit Current	540 A	

Communication				
Display	LED indicator	Color touchscreen		
Communication	CAN, RS485, RS232			

General Specification		
Dimension (WxDxH mm)	465 x 230 x 695 mm	
Weight (kg)	93 kg	
Installation	Floor Stand or Wall Mount	
Operating Temperature	Charge: 0~55°C / Discharge: -20°C ~ 55°C	
Operating / Storage Humidity	≤95% RH	
Max Operating Altitude	≤2000 m	
IP Rating	IP20	
Cell Technology	LiFePO ₄ , Lithium Iron Phosphate	
Cycle Life	6000 Cycles @ 80% DoD / 25°C / 0.5°C, 60% EOL	
Scalability	Max 63 batteries in parallel	

Standard Compliance (more available upon request) Certificates CE, UN38.3

Ordering And Deliverable Part				
Product Ordering Part	lite 10K5 Battery (Cable /wall mount included)	AIR 11K7 Battery (Cable /wall mount included)		